CONTRACT DATA REQUIREMENTS LIST

Form Approved OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 440 hours per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Department of Defensa, Washington Headquarters Services, Directorate for Information Department of Defensa, Washington Headquarters Services, Directorate for Information Department of Defensa, Washington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503. Please 00 NOT RETURN your form to either of these addresses. Send completed form to the Government Issuing Contracting Officer for the

Department of Defense, Wa Budget, Paperwork Reducti Comtract/PR No. listed in Bi	ion Project (U/U4-U188), was	es, Directorate for In shington, DC 20503.	formation Operations and Please DO NOT RETUR	Reparts, 121 N yaur form t	5 Jefferson Davis Highway, o either of these addresses.	Suite 120 Send cor	4, Arington, VA 22202-4302, and to tr npleted form to the Government Issuing	g Contract	ing Officer	for the		
A. CONTRACT LINE ITE	EM NO.	B. EXHIBIT		C. C	CATEGORY:	TM	n TH	IER X				
D. SYSTEM/ITEM TF 39 Engine/	/5365-00-114-0	1345NY	E. CONTRACT/PR				ITRACTOR				_	
1. DATA ITEM NO. 0001	2. TITLE OF DATA ITEM First Article		(FATP)			3. SUB	TITLE				[1	7. PRICE GROUP
4. AUTHORITY (Data Acquis		T COL T IMI	5. CONTRACT REFER	ENCE			6. REQUIRING OFFICE OC-ALC/LPERA	-				8. ESTIMATED TOTAL PRICE
7. DD 250 REQ	9. DIST STATEMENT REQUIRED	10. FREQU	ENCY 1	12. DATE C	OF FIRST SUBMISSION		14. DISTRIBU	1	b. COPIE	S		
8. APP CODE	-	11. AS DF	DATE	13. DATE C SUBMI	OF SUBSEQUENT SSION		a. ADORESSEE	Draft	Reg	inal Repro		
OC-ALC/ENF Tinker AFB, O	7		Ionitor, 3001	Staff 1	Drive, Ste T69		OC-ALC/ENRS		1		Г	7, PRICE GROUP
1. DATA ITEM NO. 0002	2 TITLE OF DATA ITEM First Article	Test Repo				3. SUB						
4 AUTHORITY (Data Acquis	sition Document No.)		5. CONTRACT REFER	ENCE			6. REQUIRING OFFICE	44				8. ESTIMATED TOTAL PRICE
7. DO 250 REO	9. DIST STATEMENT REQUIRED	10. FREQU	ency 1	12. DATE D	OF FIRST SUBMISSION		14. DISTRIBU	T	b. COPIE	S		
8. APP CODE		11. AS OF	DATE	13. DATE D Submis	OF SUBSEQUENT SSION		a. Addressee	Draft	F Reg	nal Repro		
18. REMARKS Send First Art OC-ALC/ENR			onitor, 3001	Staff D	Orive, Ste T69		OC-ALC/ENRS		1			
Tinker AFB, C	2. TITLE OF BATA ITEM					3. SUB	15. TOTAL		1		[7. PRICE GROUP
4. AUTHORITY (Data Acquis	ition Document No.)		5. CONTRACT REFERE	NCE			6. REQUIRING OFFICE					B. ESTIMATED
7. DD 250 REQ	9. DIST STATEMENT	10. FREQUI	ENCY	12. DATE D	F FIRST SUBMISSION		14. DISTRIBUT					TOTAL PRICE
8. APP CODE	REQUIRED	11. AS OF	DATE		F SUBSEQUENT	· · · · · ·	a. ADDRESSEE	1	b. COPIES	nal	L	
16. REMARKS	<u></u>		<u> </u>						Reg	Repro	:	
1. DATA ITEM NO	2 TITLE OF DATA ITEM					3. SUB1	15. TOTAL				F	T ADUST DOCUM
4. AUTHORITY (Data Acquisi	ition Document No.)		5. CONTRACT REFERE	NCE .		J. 3061	6. REQUIRING OFFICE					7. PRICE GROUP 3. ESTIMATED
7 DD 250 REQ	9. DIST STATEMENT	10. FREQUE			F FIRST SUBMISSION		14. DISTRIBUT	'ION	·····			TOTAL PRICE
8. APP CODE	REQUIRED	11. AS OF E	DATE	13. DATE OF	F SUBSEQUENT		a. ADORESSEE		b. COPIES	lar	L	
16. REMARKS				CODMIG				Draft	Reg	Repro		
	ıan, TF39 Eng	ineer	H. DATE 21 No	ov 03	I. APPROVED BY		15. TOTAL J.	DATE				
DD Form 1423, JI	UN 90 <i>(EF)</i>		PREVIOUS E	DITIONS AF	RE OBSOLETE.		Page of			Pages	-	

	RTICLE REQUIREMEN			1. DATE
(AFMCI 64-110, AFMCI 23-102 and FA		ditional Instructions of	1	21 Oct 03
2. P/R/MIPR NUMBER	3. PART NUMBER 9607M	36P02	4. NSN 5365-	00-114-0345NY
5. FIRST ARTICLE QUANTITY THE FIRST ARTICLE IS 3	UNIT(S) OF LOT/IT	EM		
AND WILL BE: X PART OF PRODUCTION OF				T-170 (
AND WILL BE: X PART OF PRODUCTION QU 6. ARTICLES	JANTITY	7. LONG LEAD TIME ITE	O PRODUCTION QUAN	IIIY
		7. LONG LEAD TIME THE	r	1
WILL X WILL NOT SERVE AS A STANDARD	MANUFACTURING	REQUIRED (See FAR 52.2	X 09-3 or -4, alternate II)	NOT REQUIRED
8. SPECIAL REQUIREMENT/PRODUCTION FACILITIES X REQUIRED	(See FAR 52.209-3 or -4 Alter		D	
"The First Article offered must be manufacture component not manufactured by the contractor the contract. A certification to this effect must	, such component must be m	anufactured at the faciliti	ed under the contract,	or if the First Article is a nent is to be produced for
9. TEST/INSPECTION REQUIREMENTS		F. FIRST ARTICLE	DELIVERY:	
A. X CONTRACTOR TESTING GOVERN	IMENT TESTING	(1) Due within	calendar	days from date contract.
Performance or other characteristics which the Fi are <u>drawing #9607M36</u> and all specifi	rst Articles must meet	(2) Notify	calendar day	s prior to shipment.
drawing	cations on the	·	government at	
B. The detailed technical requirements for First Arti				
contained in Verifiable dimensions on the applicable engineering notes	ne drawings and		/Sat Forth Consistence and	Address
(Cite Spec and Para number	r)	(4) Government		oval/disapproval within
C. X TEST PLAN REQUIRED		days after re	ceipt of first article pack	rage.
(1) DD Form 1423 ELIN (2) Delivery due 45 plendar days from	data of annings	G. Estimated cost o	f aovernment testing/ir	nspection evaluation.
(3) Number of days for government approval/o		.		
	equesting Activity) or to start of testing.			
E. X TEST REPORT REQUIRED				
(1) DD Form 1423 ELIN (2) Due 120 andar days from date of c	ontract.			
(3) Forwarded to OC-ALC/ENRS, Attn	: F.A. Monitor,			
3001 Staff Dr. STE T-69, Tinker A	1			
(4) Government written notice of approval/disap days after receipt of contractor's report.	proval due <u>45</u>			
10. DISPOSITION OF FIRST ARTICLES		Disapproved f	irst articles will be retu	rned to the contractor/
X pproved First Articles will be forwarded to	USAF SUPPLY	will be r	etained bystructions from the con	pending
ert quantity), first articles will be Residual components of dispproved first a returned to the contractor/ will be re	rticles will be tained by	following disp	requests designated position will apply. (NC ry Sales (FMS)).	as direct shipments the DTE: Always applicable on
pending dispos the contractor.	ition instructions from			urned to the contractor for
First articles will be installed on aircraft/ proper fit/function. Approved article aircraft/equipment and will not be forward	will remain on the ded to USAF Supply, but			ticles will remain the same
will be considered part of the contract quar	ruty.	Other Dispos	ition:	
				

11. CONDITION(S) FOR WAIVER OF FIRST ARTICLE APPROVAL	
a.	same or similar article to the prime contractor for delivery to the
b. X Offerors currently in production of the same or similar article for a received First Article approval under the existing contract.	Government X DoD, X skinfrectend who have
c. X Offerors who have previously furnished production quantities of the X Air Forcerovided articles thus furnished have exhibited satisfies	
d [v] 2	
d. X Provided not more than 36 nonths have elapsed since comple	etion of the contract.
e. First Article testing will not be waived.	
f. X See Remarks in block 12 below.	
NOTE TO BUYER: UNDER CONDITIONS A AND C ABOVE, THE COGNIZ HAS EXHIBITED SATISFACTORY PERFORMANCE IN SERVICE AND PRE THIS DECISION. THE BUYER MUST SOLICIT DUAL PRICES (That is, E FURNISH THE COGNIZANT ENGINEERING ACTIVITY WITH THE FOLLOWING	PARE AND RETAIN SUPPORTING DOCUMENTATION TO FULLY JUSTIFY ooth with and without requirement for first article approval) AND MUST
A. PROCURING OFFICE B. CONTRACT NUMBER C. DA	ATE OF CONTRACT D. SPECIFICATION NUMBER AND REVISION
12. REMARKS	
Send Contractor Reports to: OC-ALC/ENRS Attn: FIRST ARTICLE MONITER 3001 STAFF DRIVE, STE T-69	
TINKER AFB, OK 73145-3036	
Block 11(f) - All requests for waiver of First Article testing shall (OC'ALC/LPERA) for approval. First Article testing will be wait Engine Co.)	be forwarded to the cognizant engineering authority wed if the contractor is the OEM (general Electric Aircraft
Justification for First Article: The First Article is required to ver requirements for acceptance. In addition, FAR 9.3 applies.	ify that the contractor is capable of meeting all of the contract
FAI JUSTIFICATION	
THIS ITEM IS CRITICAL TO THE SAFE OPERATION AND I (BLUEPRINTS, ENGINEERING INSTRUCTIONS, ETC) CON PROCESSES AND/OR OPERATIONS WHICH REQUIRE VER PRODUCE THIS ITEM. CONDITIONS OF FIRST ARTICLE V	TAINS CLOSE TOLERANCES AND COMPLEX
13. COGNIZANT ENG ORGANIZATION RESPONSIBLE FOR CONDUCTING	14. PR INITIATOR (Name, Organization, Phone)
AND/OR APPROVING TEST (Name, Organization, Phone) Kyle Streetman	
OC-ALC/LPERA DSN:884-4689	

		PAGE	1	
TECHNICAL DATA PACKAGE - ENGINEE	RING NOTES (ENs)			
MATIONAL STOCK NUMBER	,PART NUMBER	OF	3	PAGES
5365-00-114-0345 NY	9607M36P02			
	OTES, DEFINITIONS APPLIC	ABLE	TO	
(A) ENGINEERING CRITICAL IN APPLICATION manufacturing process, controls, and te Because of its use or application, fail reliability of such an item could be ca life or serious injury, loss of a weapondamage, with direct impact on the capab emergency or to achieve wartime sustain	sting of material or end ure to maintain the high tastrophic resulting in n system or extensive se ility to respond to a na	iten est loss conda	of ary	
(B) <u>COMPLEX</u> : Items having quality chara (hidden characteristics), in the end pr conformance must be established progres ments, tests or controls applied during performance, assembly and functional op item or in conjunction with other items	oduct for which contract sively through precise m purchasing, manufacturi eration either as an ind	ual easu: ng, ivid:	re-	
(c) <u>COMMERCIAL</u> : Described in commercial standards [FAR SUBPART 46.203(a),(1)].	catalogs, drawings or i	ndust	rial	
(D) <u>CRITICAL CHARACTERISTICS</u> : Character likely to result in hazardous or unsafe maintaining or depending upon the produ formance of the tactical function of a missile, space vehicle, engine or a maj MIL-STD-105).	conditions for individu ct; or, are likely to pr major end item such as a	als w event n air	ısing, per- ccraft	•
(E) MAJOR CHARACTERISTICS: Characterist which, when defective, are likely to re usability of the product or a major end (Derived from MIL-STD-105).	sult in failure or to re	duce	the	,
(F) MINOR CHARACTERISTICS: All characte or major but for which full conformity		s cr	itical	-
THIS PRODUCT HAS BEEN DETERMINED TO BE	OR CONTAINS (AS CHECKED	BELO	V): 🗐	
Engineering critical in application	n.			
Critical characteristics.				
Major characteristics.				
Minor characteristics, all excepts	ing critical and major.			
Complex.				
Available as a comerical product.				

TECHNICAL DATA PACKAGE - ENGINEERING NOTES (ENS)

OF 3 PAGES

NATIONAL STOCK NUMBER 5365-00-114-0345 NY PART NUMBER 9607M36P02

- When materials, processes or components are to be obtained from directed sources as indicated herein or in the specifications, alternate sources may only be utilize upon prior approval by the contracting officer of this procuring activity as a deviation.
- Bidders are requested to notify the contracting officer in writing as soon as is practicable of any drawing, specification, standard or other required technical data which is of more current date/revision than that shown on the Engineering Data List.
- Contractor is authorized to the extent specified herein to use standards, specifications, and other required technical data which are of a more current date/revision than those shown on the Engineering Data List. Proposed changes to revision-in-use other than those allowed by this paragraph must be submitted in writing to the contracting officer for approval by the cognizant engineering authority.
 - a. VENDOR DRAWINGS, VENDOR MASTER DRAWINGS (MYLARS), AIRFOIL DATA, CONTOUR DATA, AND PERFORMANCE DATA: (e.g. 1234m56, 658972, AD658972, IC658972, IF-658972) Revisions specified on the ENGINEERING DATA LIST are the revisions to be used for manufacturing. Requests to use later revisions must be submitted for approval in writing to the contracting officer, along with the newer revision document, for approval by the cognizant engineering authority.
 - b. VENDOR SPECIFICATIONS, VENDOR STANDARDS, INSPECTION
 PHOTOGRAPHS: (e.g. P1TF3, PWA360, EPS14500) The revisions
 specified on the Engineering Data List form a baseline
 minimum revision status, and are the most recent revisions
 the government can provide. No revision before that shown in
 the Engineering Data List will be used. Revisions later than
 those specified in the Engineering Data List may be used provided:
 - 1. The contractor notifies the contracting officer in writing of the revision to be used, and
 - 2. The new revision does not and will not affect form, fit, or function of the part, process, or material being manufactured and/or supplied, and
 - 3. Use of the new revision will not increase the cost to the government of compensation for the product being supplied, and
 - 4. The Engineering Notes do not contain a clause specifically excluding the allowances of this paragraph.
 - C. INDUSTRY SPECIFICATIONS/STANDARDS, MILITARY SPECIFICATIONS/STANDARDS, QUALIFIED PRODUCT LIST (QPL): (e.g. AMS 5613, ANSI Y14.5, MIL-STD-130, QPL 25135) The revision to be used will be the revision in effect on the

	PAGE 3
TECHNICAL DATA PACKAGE - ENGINEERING NOTES (Ens)	OF 3 PAGES
NATIONAL STOCK NUMBER 5365-00-114-0345 NY , PART NUMBER 9607M36P02	
dates of opening of solicitation. Later revisions of the documents are approved for use provided: 1. The new revision does not and will not affect for fit, or function of the part, processes, or materia being manufactured and/or supplied and 2. Use of the new revision will not increase the cost the government of compensation for the product be supplied.	m, al t to
Lower tier specifications listed in or referenced by first ties cations may not be shown on the data lists or engineering notes panying this contract but are nonetheless required by this cont compliance. Exceptions would occur only when such lower tier re have been specifically waived or substitute specifications/requare designated herein.	accom- ract for quirements
Reports, process sheets, inspection methods sheets and all oth required by specifications imposed by this contract for contract ance which were previously required to be submitted to a prime tractor shall be held at that facility for review by government	tor compli- design con-
When prime design source specifications require or provide for tion by that prime source quality, manufacturing, laboratory or support services, these requirements or provisions do not apply contract was issued by this procuring activity. For these servi direction pertaining thereto, contact the cognizant government administration office or this procuring activity for assistance	engineering when the ces or contract

The contractor is responsible for assuring that all dimensions, conditions, tests and test results identified in these engineering notes, applicable drawings, specifications and contract quality requirements are met by themselves and their suppliers. This requirement applies to all characteristics whether those characteristics have been specifically designed as being critical, major or are those minor characteristics not specifically

engineering office of this procuring activity of all manufacturing processes and processing procedures intended for use in production of this product. Once these processes are established, no changes shall be made without prior approval of the engineering office of this procuring activity.

1 Prior to beginning of manufacture, the contractor will notify the

Serialization of each part/assembly (contract end item) is required.

designated as such.

	REVISION:								ENGINEERING DATA L	LIST		* HISTORY *
DATE:	03OCT03	DATA TECH:	1YD	۵	ORGI	ORGN SYMBOL	1	<u> </u>	LGLDCP PR NR:		APPLICATION: TF39 ENGINE	PAGE 1 OF 1
CAGE: 07482	MANUFACT GENERAL E	MANUFACTURER NAME: GENERAL ELECTRIC COMPANY	ANY				,	VEFER 3607M	REFERENCE NR: 9607M36P02	NOUN: RING, RET	NOUN : RING, RETAINING, KEYE	NSN: 5365001140345NY
CAGE	DRAWING NUMBER	NUMBER		REV	NR	SCARD	NR NR FURN DIST SHEETS CARDS CODE CODE	FURN DIST CODE CODE	NOUN		REMARKS	
07482 9607M36	07M36		_	ſs.	0001	0001	S	14	RING, RETAINING			
07482 SI	07482 SI-212,010		_	П	0000	0000	S		DRAWING INTERPRETATION			
07482 SI	07482 S1-212,010 AMENDMENT	DMENT	`		0000	0000	S	_	AMENDMENT - INTERPRETATION OF DR			
								\Box				
	-											
STANDA REI IS	STANDARD ENGINEERING TEXT RELEASE OF THIS DATA TO IS DEPENDENT UPON THE AP	DARD ENGINEERING TEXT RELEASE OF THIS DATA TO A FOREIGN-OWNED, CONTROLLED OR INFLUENCED COMPANY IS DEPENDENT UPON THE APPROVAL OF THE FOREIGN DISCLOSURE OFFICE.	EIGN-C	MANNED,	, con.	TROLLE N DISC	D OR I	NFLUE	ENCED COMPANY			
ENGINE	ERING DATA L	ENGINEERING DATA LIST REQUIREMENTS	STN						FURNISHED METHOD CODE LEGEND:		X - DATA SUPPLIED (NOT IN EDCARS).	G - GOV'T DOCUMENT.
									C - CLASSIFIED DOCUMENT.	2	R - FURNISHED BY PCD UPON REQUEST. D - DADTIAL POCHMENT FIRMISHED	O - OTHERS, CONTRACTOR
									S - FORNISHED WITH SOLICITATION: M - STABLE BASE DRAWING REQUIRED; FURNISHED WITH CONTRACT AWARD		1 1	A - DATA NOT AVAILABLE
										TOTAL TOTAL		

QUALIFICATION REQUIREMENTS FOR PROPULSION CRITICAL APPLICATION ITEMS

1. APPLICATION: These requirements apply to all critical application items with the exception of those classified as flight safety critical parts, critical safety items, flight safety parts, fracture critical parts, or durability critical parts.

2. PURPOSE:

- 2.1 This document establishes the minimum requirements, which prospective offerors must satisfy in order to obtain pre-award engineering source approval for the specified applications.
- 2.2 Engineering source approval on items is valid for only five years from date of the OC-ALC letter notifying the offeror of engineering source approval. Approved sources, which have not delivered or been contracted by the USAF to deliver the approval item this period shall be required to re-substantiate their capability. Re-substantiation shall involve documenting that no significant changes to process location, sequence, or parameters have occurred, possession of current drawings and specifications, and no significant quality deficiencies are awaiting corrective action. Significant changes or unresolved quality deficiencies may result in additional testing, or revocation of source approval status, depending on the nature and extent of the changes and/or quality deficiencies.

3. DEFINITIONS:

<u>Critical Application Item</u> - An item that is essential to weapon system performance or operation, or the preservation of life or safety of operating personnel, as determined by the Military Services.

Engineering Source Authority - The service engineering authority for technical acquisition support and cognizant engineering activity for the weapon system in which the part is used.

Original Equipment Manufacturer (OEM) - Term typically applied to the source responsible for the original design and development of a product or system. In this case it shall refer to sources primarily responsible for the design and development of an aircraft gas turbine engines, for a US DOD activity or a NATO country, e.g., Pratt & Whitney, General Electric, Rolls Royce, etc.

<u>Production Quantities</u> - Quantities which establish a reasonable level of confidence in a prospective source's ability to consistently produce components whose integrity is equivalent to that exhibited by components which originally passed substantiation testing. As a minimum it shall be considered representative of several production lots or greater quantities commensurate with those specified in current solicitations or OC-ALC annual buy projections and shall be exclusive of quantities produced in experimental or developmental programs.

<u>Critical Process</u> - A process which is capable of producing alterations in the material structure of a component which cannot normally be evaluated without destructive testing and which can compromise the mechanical properties and ultimately the reliability of the component. Processes which are considered to be significant include but are not limited to forging, casting, heat treat, fusion welding, resistance welding, furnace brazing, peening, coating, non-conventional machining (laser machining, electro-discharge machining, electro-chemical machining, chem milling, etc.) grinding titanium alloys, cleaning titanium alloys, and non-destructive inspection.

Non-destructive Inspection - In the context of this document shall refer to inspections performed on vital characteristics which cannot be measured directly without rendering the part unfit for use. These include but or not limited to fluorescent penetrant inspection, radiographic inspection, magnetic particle inspection, ultrasonic inspection, eddy current inspection, and/or holographic inspection.

4. CONTRACTOR RESPONSIBILITY STANDARDS (FAR 9-104):

- 4.1 General standards as specified in FAR 9-104.1 apply
- 4.2 Special standards as specified in FAR 9-104.2 apply
- 4.2.1 The specific special standards to be applied are determined by the conditions which form the basis of the source approval request submitted by the offeror. There are three conditions for submission of source approval requests. These conditions are categorized as follows:
- 1) <u>Category I offeror</u> A manufacturing source, which in conjunction with their subvendors, has performed all requisite processes on the same item for the OEM.
- 2) <u>Category II offeror</u> A manufacturing source, which in conjunction with their subvendors, has performed all requisite processes on a similar item for an OEM or DOD.
 - 3) Non-manufacturing source A source offering new manufactured items to be produced by a third party manufacturing source(s) under contract must satisfy the requirements specified herein for non-manufacturing sources. Non-manufacturing sources offering surplus will be evaluated using procedures specified in procedures for handling of surplus. ESA approval of non-manufacturing sources is valid only for instant procurements only. ESA approval shall be obtained for each subsequent procurement on a case by case basis. All non-manufacturing sources must be approved by the ESA prior to contract award, each time a procurement is made for a critical application item.

5. PROOF OF CAPABILITY:

5.1 The Offeror shall submit proof that they, in conjunction with their subvendors, have manufactured production quantities of the same item (Category I offerors) for the OEM, or a similar component for an OEM or the DOD (Category II offerors) within the last three years for components with propulsion system applications. **Note**: Failure to qualify as a Category I or II offeror shall result in disapproval on components with propulsion system applications

6. DOCUMENTATION REQUIREMENTS:

- 6.1 The documentation specified herein is required to substantiate proof of capability. Failure to provide any of the specified documentation shall be grounds for disapproval of the offeror.
 - 6.2 Categories I and II:
- 6.2.1 Brochures or synopses of the company's capabilities. Identify if the company seeking approval is a non-manufacturing source or the actual manufacturer.
- 6.2.2 Identification of all subvendors of major subcomponents and critical processes, previously employed in the production of the same item (Category I Offerors) or "similar

component(s) (Category II offerors) including the specific operations and/or subcomponents provided by each subvendor and their address.

- 6.2.3 Identification of all subvendors of major subcomponents and critical processes to be employed in the production of the same item and their address. The Offeror shall substantiate that all vendors of critical processes as defined in Section 3 of this document are OEM-approved sources.
- 6.2.4 The Offeror must provide a Quality Assurance Manual that accurately portrays their current quality assurance system.
 - 6.2.4.1 The Offeror's Quality Assurance System must comply with the requirements as described in this document and Higher level contract Quality Requirements, FAR 52.246-11, ISO 9001-2000, AS 9100, NATO AQAP 2070 or equivalent. Proof of compliance shall be provided and meet one of the following:
 - 6.2.4.1.1 Certified to NATO AQAP 2070, ISO 9001-2000, or AS 9100 by the American National Standards Institute (ANSI) or the International Standards Organization (ISO) in Geneva, Switzerland, or
 - 6.2.4.1.2 Approved by an Original Equipment Manufacturer (OEM) to an equivalent Quality Assurance System standard.
 - 6.2.4.1.3 Evidence from DCMC or other appropriate government Quality Assurance Representative that Quality System is compliant to NATO AQAP 2070, ISO 9001-2000, AS 9100, or equivalent.

Proof of certification/approval must be provided and must be dated within the last three years. The decision to approve or disapprove the Quality Assurance System shall only be made after a thorough review of the Offeror's Quality Assurance Manual by the cognizant engineering authority, OC-ALC/LPER.

- 6.2.5 The Offeror shall provide evidence that their calibration system is in compliance with ISO 10012-1 and ANSI/NCSL Z540-1, and that calibration standards are traceable to NIST standards.
- 6.2.6 The Offeror shall provide evidence that the quality assurance system and available expertise which currently exists within the Offeror's facility, is capable of establishing and maintaining effective process control, and otherwise ensuring the ongoing quality of all significant processes performed in-house or by sub vendors toward the manufacture of the item. Evidence shall comply with the following criteria:
- 6.2.6.1 A copy of the latest document(s) which describe and govern the quality assurance system in effect at the Offeror's facility(ies) (i.e. Company Quality Manual).
- 6.2.7 It is highly recommended that all offerors submit all Source Approval Requests (SARs) in a binder to preclude the loss of contractor data in handling. A hard or semi-hard cover notebook form (i.e. a three-ring binder or similar product), with a table a contents and tabs corresponding to the table of contents is preferable. This will significantly reduce the turn-around time for engineering evaluation as well as reduce the likelihood of oversight or loss of valuable data which could have a significant bearing on the outcome of the evaluation.

6.3 Category I Offerors:

- 6.3.1 A complete set of legible drawings for all assemblies, details, and sub-components for the same item.
- 6.3.2 A complete set of all specifications for all material and manufacturing processes identified on the drawings for the same part and subcomponents thereof. The offeror may submit the top page of each specification showing the revision or DCMC certification in lieu of providing the specifications in their entirety.
- 6.3.3 Substantiation of possession of material structure acceptance/rejection criteria referenced on drawings, material specifications, and in process specifications. This data is not available in the Government repository.
- 6.3.4 A copy of the manufacturing process sheets employed in the production of the same item for the OEM, which define all critical process parameters. Summary of manufacturing operations sheets, travelers, or routing sheets are not acceptable in lieu of manufacturing process sheets, except for some sheet metal components. In the case of the latter routing sheets, which define process sequence, forming tooling, non-conventional machining schedules, weld schedules, and braze schedules shall be provided. All schedules and technical control documents referenced in the manufacturing process sheets which specify process operating parameters shall be included. In all cases where an operation is governed by software i.e., numerically controlled or automated operations a hard copy excerpt identifying manufacturing process operating parameters must be provided. Manufacturing process sheets shall remain confidential and may be stamped "proprietary" at the discretion of the offeror. Failure to provide detailed process sheets shall constitute grounds for disapproval.
- 6.3.5 Copies of purchase orders from OEM to offerors for the same item which define quantities ordered and all technical conditions or restrictions imposed by the OEM. Copies of the most recent shipping documents applicable to the purchase order should also be provided. Shipping documents shall be stamped appropriately by the OEM to indicate full release where on-site acceptance is specified by the purchase order.
- 6.3.6 A summary of quality deficiencies experienced in manufacturing the part for which approval is sought, during the last two years of production. The summary shall include but not be limited to all Material Review Board (MRB) actions, Quality Deficiency Reports (QDRs), Laboratory Quality Review Orders (LQROs), Supplier Report of Nonconformance (SRONs), Material Deficiency Reports (MDRs) and any other pertinent documentation as well as the coordination of the President and the Quality Assurance Manager. Coordination of the government quality assurance representative shall be included as well if government source inspection was conducted. Actions taken to resolve deficiencies identified including repair, rework or replacement of parts as well as the source primarily responsible for initiating, developing, and implementing corrective actions and the status thereof must also be provided.
- 6.3.7 Identification of all proposed changes to the manufacturing process sheets submitted by offerors as proof of capability. This requirement applies regardless of whether are not they are considered to be significant changes by the offeror.
- 6.3.8 Copy of inspection method sheets used in manufacturing and final inspection, which as a minimum defines all characteristics inspected, characteristic location on the blueprint, and the instrumentation used in the inspection. The inspection method sheets shall provide a means of a 100% inspection on each part produced unless otherwise allowed by an approved sampling or statistical process control plan, which must be provided.

6.3.9 A specific description of value added by the OEM to the same item including but not limited to performance of manufacturing processes or inspections, supply of raw material, forgings, castings, or subcomponents, quality assurance surveillance of subvendors of significant processes, use of OEM tooling, fixtures, gages, or inspection master hardware, and use of OEM manufacturing process sheets or other process related data not referenced on component drawings. The Offeror shall demonstrate capability to fulfill " value added " by the OEM on the same item as determined by the cognizant engineering activity for the weapon system.

6.4 Category II Offerors:

- 6.4.1 A complete set of legible drawings for all assemblies, details, and sub-components for the same item and the similar item. ESA will determine similarity acceptability.
- 6.4.2 A complete set of all specifications for all material and manufacturing processes identified on the drawings for the similar parts and subcomponents thereof.
- 6.4.3 A top copy of the cover sheet for all material manufacturing processes identified by the drawings for the same parts and subcomponents thereof. Will include specification number, revision and date.
- 6.4.4 Substantiation of possession of material structure acceptance/rejection criteria referenced on drawings, material specifications, and in process specifications. This data is not available in the Government repository.
- 6.4.5 A copy of the manufacturing process sheets employed in the production of the similar item for the OEM or DOD, which define all critical process parameters. Summary of manufacturing operations sheets, travelers, or routing sheets are not acceptable in lieu of manufacturing process sheets, except for some sheet metal components. In the case of the latter routing sheets that define process sequence, forming tooling, non-conventional machining schedules, weld schedules, and braze schedules shall be provided. All schedules and technical control documents referenced in the manufacturing process sheets which specify process operating parameters shall be included. In all cases where an operation is governed by software i.e., numerically controlled or automated operations a hard copy excerpt identifying manufacturing process operating parameters must be provided. Manufacturing process sheets shall remain confidential and may be stamped "proprietary" at the discretion of the offeror. Failure to provide detailed process sheets shall constitute grounds for disapproval.
- 6.4.6 Identification of all manufacturing operations to be employed in the production of the item for which the offeror is seeking approval, including the specific sequence in which the operations will be performed.
- 6.4.7 Copies of purchase orders from OEM to offerors for the similar item which define quantities ordered and all technical conditions or restrictions imposed by the OEM. Copies of the most recent shipping documents applicable to the purchase order should also be provided. Shipping documents shall be stamped appropriately by the OEM to indicate full release where on-site acceptance is specified by the purchase order. In addition, if the approval item or the similar item was manufactured for P&W, the P&W Requirements Control Card and Quality Assurance Document should be provided, or document possession thereof. Also, if similar items were produced for the government, copies of the signed DD Form 250 showing government acceptance of parts produced should be included, as well as a copy of the contract.

- 6.4.8 Identification of the specific differences between the similar items and the item for which the company is seeking approval to manufacture.
- 6.4.9 A summary of quality deficiencies experienced in manufacturing the similar part(s) during the last two years of production. The summary shall include but not be limited to all Material Review Board (MRB) actions, Quality Deficiency Reports (QDRs), Laboratory Quality Review Orders (Liquors), Supplier Report of Nonconformance (SRONs), Material Deficiency Reports (MDRs) and any other pertinent documentation as well as the coordination of the President and the Quality Assurance Manager. Coordination of the government quality assurance representative shall be included as well if government source inspection was conducted. Actions taken to resolve deficiencies identified including repair, rework or replacement of parts as well as the source primarily responsible for initiating, developing, and implementing corrective actions and the status thereof must also be provided.
- 6.4.10 Copy of inspection method sheets used in manufacturing and final inspection of the similar item, which as a minimum define all characteristics inspected, characteristic location on the blueprint, and the instrumentation used in the inspection. The inspection method sheets shall provide a means of 100% inspection on each part produced unless otherwise allowed by an approved sampling or statistical process control plan that must be provided.
- 6.4.11 A specific description of value added by the OEM or DOD to the similar part(s) including but not limited to performance of manufacturing processes or inspections, supply of raw material, forgings, castings, or subcomponents, quality assurance surveillance of subvendors of significant processes, use of OEM or DOD tooling, fixtures, gages, or inspection master hardware, use of OEM/DOD manufacturing process sheets or other process related data not referenced on component drawings. The Offeror shall demonstrate capability to fulfill "value added" by the OEM on the item for which source approval is sought, as determined by the cognizant engineering activity for the weapon system.
 - 6.5 Non-manufacturing Sources other than surplus dealers:
- 6.5.1 Brochures or synopses of the company's capabilities if not previously provided. Identify if the company seeking approval is a non-manufacturing source.
- 6.5.2 Identify the source of manufacture and provide evidence that they are currently approved by the ESA for the approval item. Sources which have not produced the item in the last three years are subject to re-qualification, the extent of which is dependent upon the extent of process and facility changes made during that time and the vendor's quality history. In the event they are not a formally approved source an approval request shall be provided substantiating their capability in accordance with 6.3 or 6.4 of this document as applicable.
- 6.5.3 The Offeror shall identify all sources to be used by the manufacturer for critical processes as defined in paragraph 3 of this document, including themselves, and substantiate that they are currently approved by the ESA or the OEM per 6.2.3 of this document.
- 6.5.4 The Offeror shall provide identification of all manufacturing operations to be employed in the manufacture of the item, including the operation sequence.
- 6.5.5 The quality of the end item provided to the Government is the responsibility of the Offeror and the Offeror shall demonstrate the capability to provide the necessary quality assurance surveillance to insure the ongoing integrity of the end product in accordance with the requirements of paragraph 6.2.6 of this document.

- 7. ON-SITE VISIT: Critical processes may require on-site verification at the discretion of the ESA.
- 8. LOSS OF QUALIFICATION APPROVAL (FAR 9.207): The offeror should be aware that qualification approval may be lost per the conditions detailed in FAR 9.207.

HENRY J GAUDREAU COL

Chief, Propulsion Contracting Division

Directorate of Propulsion

7 of 7